



4. 特開 2002-80534

014682463 **Image available**

WPI Acc No: 2002-503167/200254

XRAM Acc No: C02-142981

Modified diene polymer, used for automobile tires, is produced by reacting active conjugated diene polymer having alkali metal at terminal with silsesquioxane having specific functional group

Patent Assignee: ASAHI KASEI KOGYO KK (ASAHI)

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
JP 2002080534	A	20020319	JP 2000271527	A	20000907	200254 B

Priority Applications (No Type Date): JP 2000271527 A 20000907

Patent Details:

Patent No	Kind	Lan	Pg	Main IPC	Filing Notes
JP 2002080534	A		10	C08F-036/04	

Abstract (Basic): JP 2002080534 A

NOVELTY - Silsesquioxane modified diene polymer is produced by: (1) polymerization of conjugated diene monomer or conjugated diene monomer with vinyl aromatic monomer, employing an alkali metal type initiator to give active conjugated diene polymer having alkali metal at the terminal; and (2) reacting the active conjugated diene polymer having alkali metal at the terminal with a silsesquioxane compound having specific functional group.

DETAILED DESCRIPTION - A silsesquioxane modified diene polymer is produced by: (1) polymerization of a conjugated diene monomer, or a conjugated diene monomer with a vinyl aromatic monomer by employing an alkali metal type initiator to give an active conjugated diene polymer having an alkali metal at the terminal; and (2) reacting the active conjugated diene polymer having an alkali metal at the terminal with a silsesquioxane compound having a specific functional group which is selected from alkoxy, alkoxysilyl, epoxy, glycidyl, carbonyl, ester, vinyl, styryl, chlorine atom, bromine atom and iodine atom, 1-20C hydrocarbon group to which the above-mentioned functional group is bonded, a 1-8C silyl group to which the above-mentioned functional group is bonded and siloxane group.

USE - The silsesquioxane modified diene polymer is useful for automobile tires.

ADVANTAGE - The tires produced from the silsesquioxane modified diene polymer have low rolling resistance, and high wet skid resistance, thereby show high fuel saving properties, and high damping properties.

pp; 10 DwgNo 0/0

Title Terms: MODIFIED; DIENE; POLYMER; AUTOMOBILE; PRODUCE; REACT; ACTIVE;
CONJUGATE; DIENE; POLYMER; ALKALI; METAL; TERMINAL; SILSESQUIOXANE;
SPECIFIC; FUNCTION; GROUP

Derwent Class: A12; A26; A95

International Patent Class (Main): C08F-036/04

International Patent Class (Additional): C08F-008/42; C08F-236/10

(以上)